

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61B 19/00, 17/86	A1	(11) International Publication Number: WO 98/30167 (43) International Publication Date: 16 July 1998 (16.07.98)
<p>(21) International Application Number: PCT/US98/00278</p> <p>(22) International Filing Date: 14 January 1998 (14.01.98)</p> <p>(30) Priority Data: 60/036,096 14 January 1997 (14.01.97) US</p> <p>(71) Applicant: RESEARCH CORPORATION TECHNOLOGIES, INC. [US/US]; Suite 600, 101 North Wilmot Road, Tucson, AZ 85711-3335 (US).</p> <p>(72) Inventor: VOOR, Michael, J.; 307 Oxfordshire Lane, Louisville, KY 40222 (US).</p> <p>(74) Agents: GREENLEE, Lorraine, L. et al.; Greenlee, Winner and Sullivan, P.C., Suite 201, 5370 Manhattan Circle, Boulder, CO 80303 (US).</p>	<p>(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: **BONE FIXATION PIN WITH ROTARY CUTTING TIP**

(57) Abstract

A fixation pin and methods for attaching an immobilizing device or frame to a bone or to the skull of a patient with a skeletal injury are provided. A preferred embodiment of the pin comprises an externally threaded cylindrical body having on its leading end a shoulder and a smaller diameter coaxial cylindrical post with a rotary cutting tip on its face. The post fits snugly into a hole drilled into the bone by the cutting tip without the need for a high axial force to insert and hold the post in place. Drilling the hole with a rotary cutting tip on the face of the post minimizes lateral damage to the bone. The minimal lateral bone damage and the low axial force provide for a low incidence of pin loosening and side effects such as infections secondary to loosening and headaches. The shoulder limits the depth of penetration of the cutting tip into the bone. A crescent shaped halo utilizing the fixation pin is also provided.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

BONE FIXATION PIN WITH ROTARY CUTTING TIP

This invention relates generally to orthopedic instruments used in surgery and more specifically to pins for use in bone reparation.

Background of the Invention

In cases of skeletal injuries such as broken bones and cervical spinal injuries, it is usually necessary to fix or stabilize the position of the bones or the head of a patient while the injury heals or undergoes treatment. Such fixation may require the attachment of an external fixation frame to the long bones or a traction device or halo orthosis to the skull of a patient. A commonly used device for attaching a frame to a bone structure is the fixation pin. The halo orthosis or halo traction device provides cervical spine immobilization by penetration of the outer table of the skull with fixation pins passed through a ring or "halo" surrounding the skull and attached to a rigid body vest or cast or to a traction mechanism. As used herein, "halo orthosis" refers to the entire support apparatus and "halo" refers to the ring or frame which fully or partially surrounds the skull. The external fixation frame provides long bone immobilization by penetrating each segment of the broken bone with fixation pins attached to a rigid frame.

Fixation pins are well known in the art. Typically, halo type fixation pins are screw-like devices having a threaded cylindrical body, a conical tip at the front end for penetrating at least the outer surface of a bone, and a head or depression at the rear end for coupling to a means for rotating the pin. Long bone fixation pins are typically threaded and may be self-tapping.

Many types of fixation pins have been devised and described in patents and publications. U.S. Patent 2,966,383, to Carl H. Boetcker and William A. Shafer, 1960, discloses a surgical headrest utilizing a pin having a spring-loaded conical tip with a surrounding flange.

U.S. Patent 4,978,350, to Marcel H. Wagenknecht, 1990, discloses a fixation pin having flutes similar to a twist drill cut into the threaded portion of the pin.

U.S. Patent 5,522,817, to Thomas W. Sander and Jeffery S. White, 1996, discloses a surgical bone pin having a bone penetrating element and a bioabsorbable shaft of uniform diameter.

An article "Structural Behavior of the Halo Orthosis Pin-Bone Interface: Biomechanical Evaluation of Standard and Newly Designed Stainless Steel Halo Fixation Pins" by Steven R. Garfin et al. from Spine, Vol. 11, No. 10 of 1986, pages 977-981 contains Figs. 1 and 2 on page 978 showing various pin designs. These two figures are reproduced herein as Figs. 1A-1G and Figs. 2A-2B, respectively. The alphabetic portions of the figure numbers for Figs. 1A-1G and Figs. 2A-2B herein correspond to the alphabetic reference characters in Figs. 1 and 2 of the article.

Figures 1A-1G are schematic diagrams of one standard (control) pin design and six experimental pin designs: standard tip (Fig. 1A), conical tip (Fig. 1B), cylindrical tip with sharp cutting edge (Fig. 1C), cylindrical tip with sharp cutting teeth on edge (Fig. 1D), narrow bullet tip (Fig. 1E), wide bullet tip (Fig. 1F), and bullet tip and raised cylindrical shoulder with cutting edge Fig. (1G). The authors of the article stated that "All designs but one proved unsatisfactory because of inadequate (Figure 1: C, D, E) or excessive (Figure 1: B, G) pin penetration into the calvarium. The remaining pin design (Figure 1: F, and Figure 2) used a stainless steel cylindrical tip 1.5 mm in diameter with a sharp, slightly tapered point machined on the end. The distance from the tip of the pin to the shoulder measured 2.5 mm. The choice of this distance was based on previous measurements of the mean thickness of the outer cortex of the adult calvarium. This pin design enables the cylindrical column of the pin to penetrate the outer table of the adult calvarium, but further penetration is limited by the shoulder of the pin. As a result, adequate pin penetration is achieved but excessive penetration with its serious complications is avoided."

Figures 2A and 2B are schematic diagrams showing in greater detail the experimental wide bullet tip design of Fig. 1F and the standard tip design of Fig. 1A, respectively. The control pin having the standard tip design was described in the article as a commercially available stainless steel halo fixation pin (Jerome Medical, Mt. Laurel, New Jersey).

With the potential for catastrophic complications associated with inadequate immobilization of unstable cervical spine injuries, it is important to maintain a stable connection between a halo and the skull of the patient. However, loosening of the fixation pins at the pin-bone interface is the most common complication associated with use of the halo orthosis. Pin loosening rates as high as 60% have been reported. Conclusions have typically been that loosening is reduced if the insertion torque and subsequent pin tip penetration are increased resulting in a larger axial pin fixation force into the skull surface.

Conventional conical or tapered pin tips require high axial forces to insert and hold the pins in place without loosening. For example, the aforementioned article states that a torque of 8 in-lb (0.9 N-m) applied to halo pins has been found to be safe and effective in lowering the incidence of pin loosening and infection. Eight in-lb of torque applied to a fixation pin can produce axial forces in the range of 100 to 200 pounds (450 to 900 N) depending on the material of the pin, lubrication, etc. Such high forces can be quite uncomfortable for the patient. For example, headaches are a well documented side effect of halo fixators.

It is therefore an object of this invention to provide a fixation pin which can be inserted and held in place with a small axial force and with little damage to the surrounding bone, and which can withstand repetitive transverse loading without loosening. Another object of the invention is to provide a halo orthosis which affords more comfort and better peripheral vision for the patient, greater flexibility in pin placement, and better access to the spine for treatment. A further object of the invention is to provide a method of attaching an external fixation frame to a long bone which reduces the risk of damage to tissue surrounding the bone.

Summary of the Invention

The invention provides a rotary-cutting fixation pin for attaching an immobilizing device or frame to a bone or to the skull of a patient. The pin comprises a body, a cylindrical post attached to the body, a rotary cutting tip on the face of the post, and a shoulder extending radially outward from the base of the post. Herein, when referring to a post, "base" refers to the attached end and "face" refers to the unattached end of the post. Also herein, when referring to a body or post, the word "cylindrical" means having a generally cylindrical surface but does not exclude depressions, reliefs, flats or flutes cut or formed into the cylindrical surface. The rotary cutting tip comprises cutting edges extending radially outward on the face of the post. Herein, the phrase "extending radially outward" means extending outward from the axis of a cylinder along any path having a radial component in its vector, such as a diagonal or spiral path, and may also include an axial component. The body is preferably cylindrical in shape, with a body diameter greater than the post diameter, and attached coaxially to the post. Then, preferably, the shoulder extends from the diameter of the post to the diameter of the body. Also preferably, the body has screw threads along a portion of its length, for inserting and retaining the pin in a halo or long bone, and a coupling feature for rotating the pin.

During insertion, the pin is rotated and the cutting tip is advanced into the bone. The cutting tip drills a clean cylindrical hole into the bone without requiring a large axial force. The shoulder limits the depth of penetration of the post into the bone. After insertion, the cylindrical post fits snugly in the hole and no axial force is necessary to hold the post in place.

Eliminating the need for large axial forces to insert and retain the pin in halo applications permits the use of a more comfortable halo orthosis, reduces compression damage to the bone surrounding the pin, reduces loosening of the pin in the bone, and reduces the incidence of side effects such as infections secondary to loosening and headaches resulting from continuous large axial forces over long periods of time.

The invention also provides a horseshoe shaped crescent halo and a method of attaching a long bone fixation frame, both utilizing a fixation pin of this invention.

Brief Description of the Drawings

Figures 1A-1G are schematic diagrams of various forms of prior art.

5 Figures 2A and 2B are more detailed diagrams of Figs. 1F and 1A.

Figure 3 shows a preferred embodiment of the fixation pin.

Figure 4 is a perspective view of the rotary cutting tip of the pin.

Figures 5A and 5B show variations on the embodiment of Fig. 3.

Figure 6 is a cross-sectional side view of the pin in a skull.

10 Figures 7A-7C show a crescent halo orthosis.

Figure 8 shows a flexible halo orthosis.

Figures 9A and 9B show the pin in a long bone application.

Figures 10A and 10B show the pin in a bone fragment.

Description of the Preferred Embodiment

15 In the drawings, like reference numerals indicate like features; and, a reference numeral appearing in more than one figure refers to the same element. The drawings and the following detailed descriptions show specific embodiments of the invention. Numerous specific details including materials, dimensions, and products are provided to enable a more thorough understanding of the invention.

20 However, it will be obvious to one skilled in the art that the present invention may be practiced without these specific details.

Referring to Fig. 3, fixation pin 10 comprises cylindrical body 11, cylindrical post 12 coaxially attached to the leading end of body 11, rotary cutting tip 13 formed on the face of post 12, radial shoulder 14 formed between the adjacent ends of the cylindrical surfaces of body 11 and post 12, optional screw threads 16 formed on a portion of the cylindrical surface of body 11, and optional square pin head 17 and screwdriver slot 18 formed on the trailing end of body 11. Preferably the post diameter is smaller than the body diameter and shoulder 14 extends between the post diameter and the body diameter. However, the diameter of shoulder 14 can be larger or smaller than the diameter of body 11.

In use, when inserting pin 10 into a bone, pin 10 is rotated and cutting tip 13 is advanced into the bone by screw threads 16 or by an axial force applied to body 11. As cutting tip 13 advances, a hole is drilled into the bone which fits snugly around post 12. The drilling operation can be continued until shoulder 14 contacts the bone thereby limiting the depth of penetration of post 12 into the bone. By use of cutting tip 13 on the face of post 12, the bone outside the diameter of post 12 is undamaged by the insertion and retains its structural integrity for supporting transverse loads applied to post 12 and possible axial loads applied to shoulder 14.

The leading end of body 11 is optionally tapered. Tapered section 15 permits the use of a standard diameter for body 11, for strength and compatibility with existing frames, along with a smaller diameter for shoulder 14 to minimize the area of soft tissue involvement around the pin insertion site. However, the length, shape and degree of taper (including no taper) of section 15 may vary depending on various dimensions and applications of the pin. Pin head 17, comprising four flat surfaces formed on body 11, and screwdriver slot 18 comprise optional coupling features for rotating the pin during insertion. However, other forms of coupling features well known in the art may be used. For example, a hexagonal head comprising six flat surfaces formed within the diameter of body 11 may be used instead of square head 17 or a Phillips screwdriver or Allen wrench socket can be used in place of the flat blade screwdriver slot 18. Or, either the head or the slot can be used without the

other. As a further example, an external cap can be threaded or clamped onto the pin thereby requiring no coupling feature at all.

Figure 4 is an expanded perspective view of rotary cutting tip 13 showing rotationally leading surfaces 131, rotationally trailing surfaces 132, and cutting edges 133 formed by the intersections of surfaces 132 and 133. Cutting edges 133 extend radially outward to substantially the same radius as that of post 12 to permit cutting a clean hole which fits snugly around post 12. The open space between surfaces 131 and 132 provides room for bone chips as cutting progresses. Since bone is porous, the chips occupy less space than solid bone and spiral flutes such as used in twist drills are normally not necessary. However, within the definition of cylindrical as used herein, flutes may be provided on post 12 if necessary or desired. Although four cutting edges oriented substantially perpendicular to the axis of post 12 are shown here as a preferred embodiment, it will be apparent to those of ordinary skill in the art that the cutting function can be achieved with a different number, shape or orientation of cutting edges and surfaces. For example, the cutting edges can extend axially farther out at the center of the face than at the perimeter thereby forming a point similar to that of a twist drill.

Figure 5A shows a variation on the configuration of fixation pin 10 of Fig. 3. Fixation pin 20 comprises cylindrical body 21, cylindrical post 12 coaxially attached to the leading end of body 21, rotary cutting tip 13 formed on the face of post 12, rounded shoulder 22 formed between the adjacent ends of the cylindrical surfaces of body 21 and post 12, screw threads 23 formed on a portion of the cylindrical surface of body 21 and screwdriver slot 24 formed on the trailing end of body 21. In this configuration, shoulder 22 flows smoothly from the cylindrical surface of body 21 to a surface substantially perpendicular to the axis common to body 21 and post 12. Also, the coupling feature consists of screwdriver slot 24 alone without the head 16 of Fig. 3.

Body 21 (and body 11 of Fig. 3) may be provided with flutes 25 and self-tapping threads 26 as shown in Fig. 5B for use in long bones (described later) or

without threads for use in unthreaded immobilizing devices, e.g., devices with clamps for holding the pins. Self-tapping threads 26 can have the form of a truncated cone in that the diameters of the threads decrease toward the leading end. Although body 21 and body 11 of Fig. 3 are preferably cylindrical in shape, the cylindrical surface can be modified by flutes, flats or other surfaces contained within the diameter of the cylinder. For example, a coupling feature can be formed by grinding flat surfaces on a cylindrical body for receiving a wrench. Also, for example, a pin can include surfaces, such as flats, ground or otherwise formed on all or a portion of the length, and a portion of the circumference, of a cylindrical body (for receiving a tool such as an open end wrench) while retaining enough of a cylindrical shape to fit snugly into a round or threaded hole. If the fixation pin is not required to fit into a hole in a frame or orthosis, i.e., other devices for attaching the pin to the frame are used, the body of the pin may take whatever shape is appropriate for the attaching device. For example, the attaching device can be a screw or pin inserted through the frame and into the fixation pin.

Although the post, cutting tip, body and shoulder are described and illustrated in Figs. 3, 4, 5A and 5B as integral parts of a pin, they can comprise discrete components fastened together to form a pin. For example, the shoulder can be a collar, flange or short ring formed on, or attached to, the base of the post. In this case, the post and the body adjacent to the post can have the same diameter with the shoulder having a larger diameter and thereby defining the base. Or, the shoulder can have the form of a disk captured or bonded between a discrete post and body.

Figure 6 is a cross sectional view of fixation pin 10 inserted into a skull. This view shows post 12 of pin 10 inserted, through a small incision made in the external soft tissue 19 (skin), into skull 18. Preferably, during insertion, a halo (not shown) is placed around the head of the patient and body 11 is threaded into a tapped hole in the halo. Then pin 10 is rotated via its coupling feature, which advances cutting tip 13 into skull 18. This process cuts a clean cylindrical hole into skull 18 and leaves post 12 fitting snugly in the hole with minimal surrounding bone damage and with little

or no required axial force. Alternatively, an unthreaded pin can be inserted into an unthreaded hole in a halo and rotated by a chuck clamped to the trailing end of the pin. The pin can be advanced by a low axial force applied to the pin by the chuck. When the cutting process is finished, the pin can be held in place by a clamping device in the halo. In either case, if necessary, shoulder 14 limits the depth of penetration of cutting tip 13 by contact with the outer surface of skull 18.

Because of the high axial force required to insert and prevent loosening of conventional fixation pins with conical or tapered tips, the halo portion of a halo orthosis is typically a complete, i.e., closed, ring and normally located on or near the equator of the skull to avoid slippage. The closed ring is more rigid when subjected to radial forces than an open ring of similar proportions and the skull is stronger near the equator. However, a closed ring at the equator location obstructs the peripheral vision of the patient, is uncomfortable and may limit access to the injured spine. In the current invention, the low axial force required by the fixation pin and its more effective penetration and increased fixation strength permit greater freedom in the shape and positioning of the halo. Figure 7A is a schematic diagram of a crescent halo orthosis 30 made practical by fixation pin 10. Halo orthosis 30 includes crescent halo 31 which has the shape of an elongated crescent or horseshoe. Halo 31 is tilted backward relative to the equator of skull 32. Tilting halo 31 backward removes the peripheral vision limitation and moves the front pin insertion sites from the forehead to points behind the hairline where scarring is less evident. Because of the low axial force requirements of fixation pins 10, halo 31 does not need to be a complete circle and can be open at the back of skull 32. The open back of halo 31 provides more comfort for the patient and better access to the injured spine by the surgeon and other medical personnel. Halo 31 can be mounted on a lockable pivot 33 to permit tilting halo 31 to an angle appropriate for each patient. Although halo 31 is shown attached to a vest type orthosis, it can also be used with traction devices (not shown) and other orthoses known in the art.

Figures 7B and 7C show side and plan views, respectively, of crescent halo 31. Halo 31 comprises frame 34 having a pivotal mounting feature 35 and multiple

fixation pin holes 36. Halo 31 is mounted via feature 35 on lockable pivot 33 of Fig. 7A or on a traction device (not shown). Halo 31 can be rotated about pivot 33 for initial adjustment and then locked in place by pivot 33 to immobilize the spine. Multiple fixation pin holes 36 provide flexibility in locating pins 10 on the skull.

5 A variation on the crescent halo is shown in Fig. 8. Flexible halo 41 comprises front section 42 and left and right side sections 43 and 44, each independently adjustable. Multiple fixation pin holes 36 provide flexibility in locating the pins on the skull. Sections 42, 43 and 44 include flexible mounting features 46 and 47 for
10 attaching to a lockable pivot 33 as shown in Fig. 7A or to a traction device (not shown). Sections 42, 43 and 44 can be rotated about pivot 33 to fit halo 41 to the skull and then locked in position by lockable pivot 33 to immobilize the spine.

Figure 9A is a schematic diagram of fixation pins 10 inserted into a long bone. A bone broken into two sections 52 and 53 is immobilized by external fixation frame 51 and fixation pins 10. Figure 9B is an enlarged view of the encircled portion of Fig.
15 9A showing the pin insertion in greater detail. During insertion, holes slightly smaller than the outside diameter of pins 10 are drilled into a first side 54 of bone section 52 (or 53). Then pins 10 are threaded into side 54, utilizing self-tapping threads, and advanced by rotation through the interior 56 to second side 55 of section 52. Then,
20 each pin 10 is further rotated, advancing cutting tip 13 into side 55. This process cuts a clean cylindrical hole into side 55 and leaves post 12 fitting snugly in the hole. Shoulder 14 limits the depth of penetration of cutting tip 13 into side 55. This method of attaching an external fixation frame to a long bone eliminates the risk of damage to tissue outside of bone side 55 caused by drilling and threading a conventional
25 fixation pin through both sides 54 and 55 of bone section 52 (and 53). After pins 10 are inserted into bone sections 52 and 53, they are clamped into frame 51 by conventional methods.

Figure 10A is a schematic diagram of fixation pins 10 used to stabilize a bone fragment in a long bone. A bone broken into a fragment 57 and two sections 58 and 59 is immobilized by external fixation frame 51 and fixation pins 10. Figure 10B is

an enlarged view of the encircled portion of Fig. 10A showing the pin insertion into the fragment in greater detail. In this method, frame 51 is attached to bone sections 58 and 59 as described in Figs. 9A and 9B. Then fixation pin 10 is threaded through a tapped hole in frame 41 and advanced by rotation through the external tissue (not shown) to the surface of fragment 57. Pin 10 is further rotated and cutting tip 13 is advanced into fragment 57 until shoulder 14 presses against the surface of fragment 57 thereby holding fragment 57 in place.

Although for simplicity in the drawings, Figs. 6-10B all illustrate the use of pin 10 of Fig. 3, pin 20 of Figs. 5A and 5B can be used in these applications, and may be preferred in the long-bone applications of Figs. 9A-10B.

Empirical data indicate that the fixation pin of this invention withstands transverse cycling loads at an axial pin force of 50-90 N (11-20 lb) as well as conventional pins with conical tips withstand those loads at an axial pin force of 800-900 N (180-202 lb). Measured mean transverse force for single load failure of the pin of this invention was about 1000 N (225 lb) compared to about 550 N (124 lb) for conventional pins at an axial force of 50-90 N for both pins.

In summary, the invention provides a bone fixation pin having on its leading end a shoulder attached to a cylindrical post with a rotary cutting tip on its face. During insertion, the cutting tip cuts a clean cylindrical hole into a bone and the shoulder limits the depth of penetration. After insertion, the post fits snugly in the hole without requiring axial force for retention. The pin insertion causes minimal damage to bone surrounding the hole. Low axial force is needed to insert or hold the pin in place compared to conventional halo pins. The invention also provides a horseshoe-shaped crescent halo and a method of attaching an external fixation frame, both utilizing the fixation pin of this invention.

While the invention has been described above with respect to specific embodiments, it will be understood by those of ordinary skill in the art that various

changes in form and details may be made therein without departing from the spirit and scope of the invention.

Claims

What is claimed is:

- 1 1. A fixation pin, comprising:
 - 2 a cylindrical post having a post diameter, a base and a face;
 - 3 a rotary cutting tip formed on said face;
 - 4 a shoulder extending radially outward from said base; and
 - 5 a body attached to said base.
- 1 2. The fixation pin of claim 1 wherein said cutting tip comprises a cutting edge
2 formed by an intersection of a rotationally leading surface and a rotationally
3 trailing surface, said surfaces contained within said post diameter.
- 1 3. The fixation pin of claim 1 wherein said body includes a cylindrical section
2 having a body diameter, said cylindrical section attached to said base coaxially
3 with said post.
- 1 4. The fixation pin of claim 3 wherein said body includes a surface formed on
2 said body within said body diameter.
- 1 5. The fixation pin of claim 3 wherein said shoulder comprises a flange.
- 1 6. The fixation pin of claim 3 further comprising a tapered section formed on said
2 body adjacent to said shoulder, said shoulder having a shoulder diameter not
3 limited to said body diameter.

- 1 7. The fixation pin of claim 3 further comprising a screw thread formed on said
2 cylindrical section.
- 1 8. The fixation pin of claim 7 further comprising self-tapping flutes formed in said
2 body.
- 1 9. The fixation pin of claim 7 wherein a portion of said screw thread has a
2 truncated cone shape.
- 1 10. The fixation pin of claim 1 further comprising a coupling feature for rotating
2 said fixation pin.
- 1 11. The fixation pin of claim 10 wherein said coupling feature is a screwdriver slot.
- 1 12. The fixation pin of claim 10 wherein said coupling feature comprises a surface
2 formed on said body for connecting a rotating device to said pin.
- 1 13. A fixation pin, comprising:
2 a cylindrical post, having a base, a face and a post diameter;
3 a rotary cutting tip formed on said face, said tip comprising a cutting edge
4 formed by an intersection of a rotationally leading surface and a rotationally
5 trailing surface, said surfaces contained within said post diameter; and
6 a shoulder extending radially outward from said base; and
7 a body having a cylindrical section with a body diameter, said cylindrical
8 section attached coaxially to said post.

1 14. The fixation pin of claim 13 further comprising a tapered section formed on
2 said body adjacent to said shoulder, said shoulder having a shoulder diameter
3 not limited to body diameter.

1 15. The fixation pin of claim 13 further comprising a screw thread formed on said
2 cylindrical section.

1 16. A method of attaching a halo to a skull, comprising the steps of:

2 providing a fixation pin comprising a cylindrical post having a base and a face,
3 a rotary cutting tip formed on the face, a shoulder extending radially outward
4 from the base, and a body attached to the base;

5 placing the halo around the skull;

6 inserting the pin through the halo;

7 rotating and advancing the cutting tip into the skull; and

8 securing the pin to the halo.

1 17. A method of attaching an external fixation frame to a bone, comprising the
2 steps of:

3 providing a fixation pin, the pin comprising:

4 an elongated cylindrical body having a body diameter;

5 a screw thread formed on the body;

6 a cylindrical post, having a base, a face and a post diameter smaller
7 than the body diameter, coaxially attached to the body;

8 a rotary cutting tip formed on the face; and
9 a shoulder extending radially outward from the base;
10 drilling a hole into a first side of the bone;
11 threading the body into the hole;
12 rotating and advancing the cutting tip into a second side of the bone; and
13 attaching the pin to the frame.

1 18. The method of claim 17 wherein the screw threads are self-tapping.

1 19. A crescent halo, for attaching to a skull, comprising:

2 a frame, for partially encircling said skull;

3 a plurality of fixation pin holes in said frame for receiving and retaining a
4 fixation pin according to claim 1; and

5 a mounting feature on said frame for attaching said frame to an immobilizing
6 device.

1 20. The crescent halo of claim 19 wherein said frame comprises a plurality of
2 independently adjustable sections.



FIG. 1A FIG. 1B FIG. 1C FIG. 1D FIG. 1E FIG. 1F FIG. 1G

2/9




FIG. 2A




FIG. 2B

3/9




FIG.3

4/9




FIG. 4




FIG. 5B

FIG. 5A

5/9




FIG.6

6/9




FIG. 7A

7/9




FIG. 7B




FIG. 7C

8/9




FIG. 8

9/9




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 98/00278

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61B19/00 A61B17/86

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	S. R. GARFIN ET AL.: "Structural Behavior of the Halo Orthosis Pin - Bone Interface : Biomechanical Evaluation of Standard and Newly Designed Stainless Steel Halo Fixation Pins" SPINE, vol. 11, no. 10, 1986, pages 977-981, XP002064593 cited in the application see figure 1D	1-4, 6, 7, 10-15
X	FR 2 707 863 A (J. C. BARBA) 27 January 1995 see page 2, line 14 - line 27 see page 4, line 15 - line 27	1-4, 7
A	see figures 1, 3	13
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

12 May 1998

Date of mailing of the international search report

28.05.98

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Nice, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/00278

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2 494 792 A (F.A.BLOOM) 17 January 1950 see column 1, line 48 - column 2, line 32; figures 1-3 ---	19,20
X	US 5 456 266 A (C.C.BROWN) 10 October 1995 see column 4, line 5 - line 14; figures 1,2A ---	19
X	US 4 612 930 A (P.W.BREMER) 23 September 1986 see figures 1,2 ---	19
A	DE 41 20 393 C (AESCULAP) 11 June 1992 see column 3, line 58 - line 65; figures 1,2 ---	1,3,7,10
A	US 2 966 383 A (C.H.BOETCKER ET A.) 27 December 1960 cited in the application see figure 1 ---	5,20
A	US 2 393 982 A (J.F.GIESEN) 5 February 1946 see page 2, line 30 - line 32; figure 23 -----	8,9

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 98/00278

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 16-18
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 98/00278

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-15

Fixation pin

2. Claims: 19-20

Crescent halo

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/00278

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 2707863 A	27-01-1995	NONE	
US 2494792 A	17-01-1950	NONE	
US 5456266 A	10-10-1995	US 5490832 A	13-02-1996
US 4612930 A	23-09-1986	JP 7083750 B JP 61257640 A	13-09-1995 15-11-1986
DE 4120393 C	11-06-1992	EP 0522242 A ES 2081514 T	13-01-1993 01-03-1996
US 2966383 A	27-12-1960	NONE	
US 2393982 A	05-02-1946	NONE	